



# Super Skid HSS Series

## Hot-Water Pressure Washers

#1 in North America for  
High-Pressure Cleaning Equipment

### Diesel-Fired / Diesel Engine

**Upright, diesel-fired burner** with stainless-steel coil skin is highly efficient and maintains constant hot water using diesel fuel

**Thermal rupture disk** protects machine and user from thermal expansion

**Adjustable high-pressure detergent injection** ensures high-pressure sudsing for better cleaning

**Water resistant control panel** includes adjustable temperature control, heavy-duty heater switch, hour meter, volt meter and keyed ignition switch

**Steam combination control** for more efficient cleaning of oils and grease

**2000 Watt Generator**

**Ready plumbed** for connection to remote water tank

**Large float tank** maintains constant pressure and flow while preventing sediment from entering the machine's components

**48 Gallon fuel tank** for long hours of use – includes fuel gauge in cap

**Model HSS-102589E:**  
9.5 GPM @ 2500 PSI

**Hotsy® triplex, tri-belt drive, positive-displacement pump** carries a 7-year warranty



Powered by **Lombardini** liquid cooled diesel engines



**3/4-inch schedule 80 heating coil** carries a 5-year warranty

**Rugged square tube frame** (standard on all HSS Series models) protects machine's vital components

**Fuel/water separator** prolongs fuel pump life

**50-ft. of two-wire, heavy-duty abrasion resistant hose**

**Heavy-duty trigger gun and wand** with insulated cool grips

### FEATURES

- Diesel-Fired and Diesel Powered / Belt Drive
- 4.8 to 9.5 GPM / 2500 to 3200 PSI
- Completely Self-Contained
- All models feature 2000 Watt Generator

[www.Hotsy.com](http://www.Hotsy.com)

Nothing Cleans Like a Hotsy!

# Super Skid HSS Series Hot Water Pressure Washers

■ Diesel-Fired / Diesel Powered ■ 4.8 to 9.5 GPM / 2500 to 3200 PSI ■ Belt Drive / Electric Start ■ Completely Self-Contained

## Designed for tough, industrial cleaning.

### SPECIFICATIONS

### BELT DRIVE

MODEL	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU / HR	PUMP MODEL	HOSE	DIMENSIONS	SHIP WT (lbs)
HSS-503089E	4.8	3000	Kohler KDW702	686	120V AC	620,000	Triplex HHC930R.1	50'-3/8"	66"l x 37"w x 53"h	1580
HSS-603289E	6.3	3200	Kohler KDW1003	1028	120V AC	620,000	Triplex HX8030R.1	50'-3/8"	66"l x 37"w x 53"h	1650
HSS-803089E	7.8	3000	Kohler KDW1003	1028	120V AC	920,000	Triplex HX8030R.1	50'-1/2"	73"l x 37"w x 64"h	1990
HSS-102589E	9.5	2500	Kohler KDW1003	1028	120V AC	920,000	Triplex HX1025R.1	50'-1/2"	73"l x 37"w x 64"h	1990

All Models are Electric Start and include a 2000W Generator 12V battery is required for all models, but is not supplied



### Clean better with Hotsy detergents

Hotsy pressure washers and parts washers clean best when matched with specially formulated Hotsy detergents. More than 40 liquids and powders meet every cleaning need imaginable. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

### Spend some time with a Hotsy Expert

Hotsy has more than 130 local distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Over 80% of Hotsy's distributors have been supporting Hotsy systems for more than 20 years.

This seasoned network of local application specialists will ensure you get the safest, most effective and most efficient cleaning solution to your specific cleaning need.



### Hotsy Accessories customize your application for top performance

High-pressure turbo nozzles



High-pressure hoses from 30 to 150-ft. lengths

Smart phone users scan this code to go the Hotsy website



Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631  
 www.Hotsy.com email: info@Hotsy.com  
 P/N 8.914-184.0 Effective 4/11 Specifications and product descriptions subject to change without notice. ©2011 Hotsy



NOTE: We are constantly improving and updating our products. Consequently, pictures, features and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.